


# Dies for RFA-4005-20 Crimp Tool Handle



**RF Connectors**, Division of RF Industries, 7610 Miramar Rd, San Diego, CA 92126  
 (800) 233-1728, (858) 549-6340, fax: (858) 549-6345, rfi@rfindustries.com, www.rfindustries.com

Crimp Dies for RFA-4005-20.indd

**RFA-4005-01**



For RG-58/U, RG-59/U, RG-142/U, RG-223/U, RG-400/U, RG-8X, Proflex and various video cables, cavity dimensions: .052", .068", .100", .213" and .255".

**RFA-4005-02**





For RG-8/U, RG-213/U, RG-214/U, and Belden 9913 cables, cavity dimensions: .100", .128" and .429". The .128" cavity crimps the center pin on Belden 9913 cable.

**RFA-4005-04**




.239", .068", .319", for RG-58/U, RG-59/U, RG-62/U and Cambridge Connectors Series CP-88 and CP-89

**RFA-4005-05**



.155", .184", and .215

**RFA-4005-06**




.255", .324", .354" for RG-59/U, RG-6/U, and F-Type (CATV) coax connectors

**RFA-4005-07**



.213", .178", .068", .042", for RG-58/U, RG-174/U coax connectors (RFI Cable Groups B & C)

**RFA-4005-08**



.318", .255", .068", .042", for RG-59/U and Belden 8281 coax cable (RFI Cable Groups D & G)

**RFA-4005-09**



.178", .130", .068", for RG-174/U, RG-188/U, RG-316/U and Mini 59/U coax connectors (RFI Cable Group B)

**RFA-4005-10**



.080", .100", .429" for RG-8/U, RG-11/U and RG-213/U (RFI Cable Group E)

**RFA-4005-12**



For RJ-45, 8 position keyed or non-keyed modular plug, with stripping and cutting for 8 conductors wire

**RFA-4005-14**




Crimps coaxial connectors on Belden 9913, LMR®-400; .429", .118" hex cavities

**RFA-4005-15**




For RJ-11, 2, 4 or 6 position modular plug, with stripping and cutting for 2, 4, 6 conductors wire



**RFA-4005-16**




For 6 DEC plug, with stripping and cutting for 6 conductors wire



**RFA-4005-17**




For RJ-45 amp plug, with stripping and cutting for 8 conductors wire



**RFA-4005-18**



For 10 position modular plug with stripping and cutting for 10 conductors wire



**RFA-4005-21**



For non-insulated terminals AWG 22-8



**RFA-4005-22**



For non-insulated flag terminals from 0.5 to 2.5 sq.mm. AWG 22-18, 16-14



**RFA-4005-23**



For cord end terminals from 0.5 to 10 sq.mm. AWG 22-8



**RFA-4005-24**




For insulated terminals from 0.5 to 6 sq.mm. AWG 22-18, 16-14, 12-10



**RFA-4005-25**



For non-insulated open barrel terminal from 0.5 to 6 sq.mm. AWG 22-18, 16-14, 12-10



**RFA-4005-26**



For non-insulated terminals and cable lugs from 1.5 to 6 sq.mm. AWG 22-18, 16-14, 12-10



**RFA-4005-27**



For non-insulated terminals DIN 46234 from 0.5 to 10 sq.mm. AWG 22-18, 16-14, 12-10, and 8

