

VERSATILE AND ECONOMICAL COAX CRIMP & STRIP KIT



- Ratchet crimp handle (shown below)
- Coaxial stripper (shown below)
- 10 changeable die sets
- Crimps hex cavities from 0.042 to 0.429 inch across the flats
- Crimps most coaxial connectors and contacts
- Rugged, foam-lined case



RATCHET CRIMP HANDLE (RFA-4005-20)

- Ratchet action with auto release with completed crimping
- High-carbon, heat-treated stamped steel
- Smooth, rapid die closure
- Disengagement lever for quick release
- Simple adjustment for die size and pressure requirements

COAX STRIPPING TOOL WITH ADJUSTABLE BLADES (RFA-4087)



RFA-4087

Features:

- Die cast zinc body
- Adjustable blade
- Two or three step stripping
- 9.25mm to 10.8mm (.364 to .425 inches)
- Cable jacket diameter
- For RG-8, 11, 213, 214/U, 9913 AND 9914
- Perfect for larger coax stripping needs

NOTE: This tool is designed to produce the primary cuts. You will need to refer to the strip length dimensions on our drawing and manually adjust the final cuts accordingly.

1.



Easily remove self-stored wrench.



REPLACEMENT BLADES
(6 PER PACKAGE)
RFA-4087-R14

2.



Adjust to meet your stripping dimensions.

3.



Give it a twirl!

COAX HEX DIES FOR RFA-4005-20 CRIMPER

Buy separately or with tool

Specific Die	Part Number for Die with Crimp Tool in Cardboard Box
RFA-4005-01	RFA-4005-400
RFA-4005-02	RFA-4005-300
RFA-4005-04	RFA-4005-304
RFA-4005-05	RFA-4005-305
RFA-4005-06	RFA-4005-306
RFA-4005-07	RFA-4005-307
RFA-4005-08	RFA-4005-308
RFA-4005-09	RFA-4005-309
RFA-4005-10	RFA-4005-310
RFA-4005-14	RFA-4005-314



RFA-4005-01

RG-58/U, RG-59/U, RG-142/U, RG-223/U, RG-400/U, RG-8X, Proflex and various video cables, cavity dimensions: .052", .068", .100", .213" and .255".



RFA-4005-07

.213", .178", .068", .042", for RG-58/U, RG-174/U, RG-316/U Coax Connectors (RFI Cable Groups B and C)



RFA-4005-02

RG-8/U, RG-213/U, RG-214/U, and Belden 9913 cables, cavity dimensions: .100", .128" & .429". The .128" cavity crimps the center pin on Belden 9913 cable.



RFA-4005-08

.324", .255", .068", .042", for RG-59/U and Belden 8281 Coax Cable (RFI Cable Groups D and G)



RFA-4005-04

.228", .068", .305", for RG-58/U, RG-59/U, RG-62/U and Cambridge Connectors Series CP-88 & CP-89



RFA-4005-09

.178", .128", .068", for RG-174/U, RG-188/U, RG-316/U and Mini 59/U Coax Connectors (RFI Cable Group B)



RFA-4005-05

.155", .184", .215"




RFA-4005-10

.080", .100", .429" for RG-8/U, RG-11/U and RG-213/U (RFI Cable Group E)



RFA-4005-06

.255", .324", .354" for RG-59/U, RG-6/U, and F-Type (CATV) Coax Connectors



RFA-4005-14

Belden 9913, LMR[®]-400, WBC-400 (RFI Cable Group I); .429", .118" hex cavities