

NNHH-65A-R4-V2

8-port sector antenna, 4x 698–896 and 4x 1695–2360 MHz, 65° HPBW, 4x RETs



- Array configuration provides capability for 4T4R (4x MIMO) on Low band and High band
- Optimized SPR performance across all operating bands
- Excellent wind loading characteristics
- Optimized for rooftop applications – Heavily suppressed lower sidelobes for elevation pattern

General Specifications

Antenna Type	Sector
Band	Multiband
Color	Light gray
Effective Projective Area (EPA), frontal	0.52 m ² 5.597 ft ²
Effective Projective Area (EPA), lateral	0.17 m ² 1.83 ft ²
Grounding Type	RF connector inner conductor and body grounded to reflector and mounting bracket
Performance Note	Outdoor usage Wind loading figures are validated by wind tunnel measurements described in white paper WP-112534-EN
Radome Material	Fiberglass, UV resistant
Radiator Material	Aluminum Low loss circuit board
Reflector Material	Aluminum
RF Connector Interface	4.3-10 Female
RF Connector Location	Bottom
RF Connector Quantity, high band	4
RF Connector Quantity, low band	4
RF Connector Quantity, total	8

Remote Electrical Tilt (RET) Information, General

RET Hardware	CommRET v2
RET Interface	8-pin DIN Female 8-pin DIN Male
RET Interface, quantity	1 female 1 male

Dimensions

Width	498 mm 19.606 in
--------------	--------------------

NNHH-65A-R4-V2

Length 1499 mm | 59.016 in
Depth 197 mm | 7.756 in

Array Layout



Array	Freq (MHz)	Conns	RET (MRET)	AISG RET UID
R1	698-896	1-2	1	CPxxxxxxxxxxxxxxxxmm.1
R2	698-896	3-4	2	CPxxxxxxxxxxxxxxxxmm.2
Y1	1695-2360	5-6	3	CPxxxxxxxxxxxxxxxxmm.3
Y2	1695-2360	7-8	4	CPxxxxxxxxxxxxxxxxmm.4

Left Bottom Right

(Sizes of colored boxes are not true depictions of array sizes)

Port Configuration



Electrical Specifications

NNHH-65A-R4-V2

Impedance	50 ohm
Operating Frequency Band	1695 – 2360 MHz 698 – 896 MHz
Polarization	±45°
Total Input Power, maximum	900 W @ 50 °C

Remote Electrical Tilt (RET) Information, Electrical

Protocol	3GPP/AISG 2.0 (Multi-RET)
Power Consumption, idle state, maximum	1 W
Power Consumption, normal conditions, maximum	8 W
Input Voltage	10–30 Vdc
Internal RET	High band (2) Low band (2)

Electrical Specifications

Frequency Band, MHz	698–806	806–896	1695–1880	1850–1990	1920–2180	2300–2360
Gain, dBi	13.3	13.7	16.7	17.1	17.4	18.2
Beamwidth, Horizontal, degrees	70	66	62	63	63	61
Beamwidth, Vertical, degrees	16.7	14.9	7.4	6.9	6.5	5.8
Beam Tilt, degrees	2–16	2–16	2–12	2–12	2–12	2–12
USLS (First Lobe), dB	14	12	14	16	17	20
Front-to-Back Ratio at 180°, dB	33	36	33	36	35	33
Isolation, Cross Polarization, dB	25	25	25	25	25	25
Isolation, Inter-band, dB	25	25	25	25	25	25
VSWR Return loss, dB	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0
PIM, 3rd Order, 2 x 20 W, dBc	-150	-150	-150	-150	-150	-150
Input Power per Port at 50°C, maximum, watts	300	300	300	250	250	200

Electrical Specifications, BASTA

Frequency Band, MHz	698–806	806–896	1695–1880	1850–1990	1920–2180	2300–2360
Gain by all Beam Tilts, average, dBi	13.1	13.5	16.2	16.8	17.1	17.9
Gain by all Beam Tilts Tolerance, dB	±0.4	±0.3	±0.7	±0.5	±0.4	±0.5
Gain by Beam Tilt, average,	2° 13.1	2° 13.4	2° 16.0	2° 16.5	2° 16.8	2° 17.7

NNHH-65A-R4-V2

dBi	9° 13.1 16° 12.9	9° 13.5 16° 13.4	7° 16.3 12° 16.2	7° 16.9 12° 16.8	7° 17.2 12° 17.0	7° 18.0 12° 17.7
Beamwidth, Horizontal Tolerance, degrees	±5.3	±3.6	±9.7	±2.8	±2.6	±5.4
Beamwidth, Vertical Tolerance, degrees	±1.1	±0.9	±0.5	±0.3	±0.5	±0.2
USLS, beampeak to 20° above beampeak, dB	15	12	14	16	17	17
Front-to-Back Total Power at 180° ± 30°, dB	23	23	29	29	27	28
CPR at Boresight, dB	24	25	17	22	22	17
CPR at Sector, dB	13	9	8	6	7	8

Mechanical Specifications

Wind Loading at Velocity, frontal	123.4 lbf @ 150 km/h 549.0 N @ 150 km/h
Wind Loading at Velocity, lateral	183.0 N @ 150 km/h 41.1 lbf @ 150 km/h
Wind Loading at Velocity, maximum	160.1 lbf @ 150 km/h 712.0 N @ 150 km/h
Wind Loading at Velocity, rear	101.6 lbf @ 150 km/h 452.0 N @ 150 km/h
Wind Speed, maximum	241 km/h 149.75 mph

Packaging and Weights

Width, packed	608 mm 23.937 in
Depth, packed	352 mm 13.858 in
Length, packed	1682 mm 66.221 in
Net Weight, without mounting kit	31 kg 68.343 lb
Weight, gross	43.4 kg 95.681 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant



Included Products

NNHH-65A-R4-V2

BSAMNT-3 – Wide Profile Antenna Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.

* Footnotes

Performance Note Severe environmental conditions may degrade optimum performance