

UA-3C



PIM free angle adapter, polymer, 3/4 in through hole

- Includes torque stop set bolt to ensure proper attachment force

Product Classification

Product Type	Adapter
Ordering Note	CommScope® standard product in Asia Pacific CommScope® standard product in the United States and Canada

General Specifications

Adapter Type	Angle adapter
Color	Black
Mounting	3/4 in through hole
Patent Number	For patents see: www.cs-pat.com

Dimensions

Height	44.958 mm 1.77 in
Outside Width	49.022 mm 1.93 in
Inside Length	25.4 mm 1 in
Outside Length	42.672 mm 1.68 in
Compatible Diameter, maximum	11.113 mm 0.438 in
Compatible Diameter, minimum	3.175 mm 0.125 in
Material Thickness	3.175 mm 0.125 in

Material Specifications

Material Type	Engineered plastic
----------------------	--------------------

Mechanical Specifications

Installation Torque, maximum	4 ft lb 5.423 N-m
Installation Torque, minimum	3 ft lb 4.067 N-m

UA-3C

Maximum Loading Triple stack, 1/2 in cable

Environmental Specifications

Operating Temperature -20 °C to +85 °C (-4 °F to +185 °F)

UV Resistance, minimum with no degradation =1000 hours

Packaging and Weights

Height, packed 25 cm | 9.843 in

Width, packed 14 cm | 5.512 in

Length, packed 12 cm | 4.724 in

Packaging quantity 10

Weight, gross 0.5 kg | 1.102 lb