

T-25-UW-NM



Termination Load, 0–6000 MHz

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Product Type	Termination Load

General Specifications

Device Type	Termination Load
Application	Indoor/Outdoor
Color	Black
Inner Contact Plating	Silver
Interface	N Male
Outer Contact Plating	Trimetal

Dimensions

Length	81 mm 3.189 in
Diameter, maximum	35 mm 1.378 in

Electrical Specifications

Average Power, maximum	25 W
Impedance	50 ohm
Operating Frequency Band	0 – 6000 MHz
VSWR	1.15

Environmental Specifications

Operating Temperature	-35 °C to +50 °C (-31 °F to +122 °F)
Relative Humidity	Up to 100%

T-25-UW-NM

Ingress Protection Test Method IEC 60529:2001, IP65

Packaging and Weights

Height, packed 98 mm | 3.858 in

Width, packed 53 mm | 2.087 in

Length, packed 58 mm | 2.283 in

Weight, gross 0.2 kg | 0.441 lb

Weight, net 0.18 kg | 0.397 lb

Regulatory Compliance/Certifications

Agency

ISO 9001:2015

Classification

Designed, manufactured and/or distributed under this quality management system

