

## Double Click-on Hanger for 1/2 in coaxial cable



### Product Classification

<b>Product Type</b>	Hanger kit
<b>Ordering Note</b>	CommScope® standard product in the United States and Canada

### General Specifications

<b>Cables per Hanger</b>	2
<b>Color</b>	Black
<b>Hanger Type</b>	Click-on hanger
<b>Mounting</b>	Mounting hole clearance for 3/8, 16 UNC or M10 threaded rod

### Dimensions

<b>Height</b>	51.054 mm   2.01 in
<b>Maximum Stack Height</b>	3
<b>Width</b>	44.958 mm   1.77 in
<b>Length</b>	88.9 mm   3.5 in
<b>Compatible Diameter, maximum</b>	16.256 mm   0.64 in
<b>Compatible Diameter, minimum</b>	15.24 mm   0.6 in
<b>Nominal Size</b>	1/2 in

### Electrical Specifications

<b>Return Loss Effect</b>	0.1 dB
<b>DTF Effect</b>	0.1 dB

### Material Specifications

<b>Material Type</b>	Engineered plastic
----------------------	--------------------

### Mechanical Specifications

# L4CLICK

---

**Vibration Survival** ≥4 hours at resonant frequency

## Environmental Specifications

**Operating Temperature** -40 °C to +85 °C (-40 °F to +185 °F)

**Environmental Strength Capability** Double cable weight

**UV Resistance, minimum with no degradation** ≥100 hours exposure in accelerated UV life chamber

## Packaging and Weights

**Height, packed** 19 cm | 7.48 in

**Width, packed** 8 cm | 3.15 in

**Length, packed** 17 cm | 6.693 in

**Packaging quantity** 10

**Weight, gross** 0.26 kg | 0.573 lb

## Regulatory Compliance/Certifications

### Agency

ISO 9001:2015

### Classification

Designed, manufactured and/or distributed under this quality management system



## \* Footnotes

**Maximum Stack Height** Fiber, Hybrid, Power