

42396A-9



Butterfly Hanger for 5/8 in coaxial cable and elliptical waveguide 127 and 132

Product Classification

Product Type	Hanger kit
Ordering Note	CommScope® non-standard product

General Specifications

Cables per Hanger	1
Color	Silver
Hanger Type	Standard butterfly hanger
Mounting	3/8 in (M10) drilled cable ladder

Dimensions

Height	33.274 mm 1.31 in
Width	38.1 mm 1.5 in
Length	42.672 mm 1.68 in
Compatible Diameter, maximum	22.022 mm 0.867 in
Compatible Diameter, minimum	20.828 mm 0.82 in
Nominal Size	5/8 in

Electrical Specifications

Return Loss Effect	0.1 dB
DTF Effect	0.1 dB

Material Specifications

Material Type	Stainless steel
----------------------	-----------------

Mechanical Specifications

Vibration Survival	≥4 hours at resonant frequency
---------------------------	--------------------------------

42396A-9

Environmental Specifications

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Corrosion Resistance, minimum with no degradation	≥500 hours in salt spray chamber
Environmental Strength Capability	Double cable weight

Packaging and Weights

Height, packed	26 cm 10.236 in
Width, packed	9 cm 3.543 in
Length, packed	9 cm 3.543 in
Packaging quantity	10
Weight, gross	0.48 kg 1.058 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant

