



TTS3-7515

Three-way Stand-off Adapter for 0.75–1.5 in round members

POWERED BY



General Specifications

Adapter Type	Stand-off adapter
Material Type	Stainless steel
Package Quantity	10

Mechanical Specifications

Material Thickness	2.591 mm 0.102 in
Maximum Loading	Double stack, 1-5/8 in cable
Mounting	3/4 in through hole

Packed Dimensions

Height	12.0 cm 4.7 in
Length	1.0 cm 0.4 in
Shipping Weight	0.58 kg 1.28 lb
Width	11.0 cm 4.3 in

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

Included Products

UAAI — Universal Angle Adapter Insert

SA-38 — Universal Stand-off Adapter

31670-1 — Round Member Adapter for 1–2 in round members

POWERED BY



UAAI

Universal Angle Adapter Insert

Dimensions

Outside Length	25.40 mm 1.00 in
Outside Width	12.70 mm 0.50 in

General Specifications

Adapter Type	Adapter
Material Type	Stainless steel
Package Quantity	10

Mechanical Specifications

Material Thickness	12.700 mm 1/2 in
Maximum Loading	Triple stack, 1-5/8 in cable
Mounting	3/8 in tapped hole

Packed Dimensions

Height	4.0 cm 1.6 in
Length	1.0 cm 0.4 in
Shipping Weight	0.13 kg 0.28 lb
Width	5.0 cm 2.0 in

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

POWERED BY



SA-38

Universal Stand-off Adapter

Dimensions

Outside Length	193.04 mm 7.60 in
Outside Width	98.04 mm 3.86 in

General Specifications

Adapter Type	Adapter
Material Type	Stainless steel
Package Quantity	10

Mechanical Specifications

Material Thickness	2.591 mm 0.102 in
Maximum Loading	Double stack, 1-5/8 in cable
Mounting	3/4 in through hole

Packed Dimensions

Height	12.0 cm 4.7 in
Length	1.0 cm 0.4 in
Shipping Weight	0.58 kg 1.28 lb
Width	11.0 cm 4.3 in

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

POWERED BY



31670-1

Round Member Adapter for 1–2 in round members

Dimensions

Compatible Diameter, maximum 50.800 mm | 2.000 in
Compatible Diameter, minimum 25.400 mm | 1.000 in

General Specifications

Adapter Type Round member adapter
Material Type Stainless steel
Package Quantity 10

Mechanical Specifications

Material Thickness 0.711 mm | 0.028 in
Maximum Loading Triple stack, 1-5/8 in cable

Packed Dimensions

Height 15.0 cm | 5.9 in
Length 10.0 cm | 3.9 in
Shipping Weight 0.23 kg | 0.50 lb
Width 10.0 cm | 3.9 in

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU
China RoHS SJ/T 11364-2006
ISO 9001:2008

Classification

Compliant
Below Maximum Concentration Value (MCV)
Designed, manufactured and/or distributed under this quality management system

