

2180SEM



Fixed-tuned PDR180 for elliptical waveguide 180

Product Classification

Product Type Elliptical waveguide connector

General Specifications

Attachment Method Tab-flare | Tool-flare
Body Style Straight, fixed-tuned
Inner Contact Plating Unplated
Interface PDR180
Outer Contact Plating Unplated
Pressurizable Yes

Dimensions

Width 38.1 mm | 1.5 in
Length 88.138 mm | 3.47 in
Transition Length 50.8 mm | 2 in
Waveguide Size WR51 | WG19 | R180

Electrical Specifications

Insertion Loss, typical 0.01 dB
Operating Frequency Band 17.7 – 19.7 GHz
Peak Power at Frequency, maximum 15.70 kW @ 18.70 GHz

Material Specifications

Material Type Brass

Environmental Specifications

2180SEM

Operating Temperature	-55 °C to +85 °C (-67 °F to +185 °F)
Storage Temperature	-55 °C to +85 °C (-67 °F to +185 °F)

Packaging and Weights

Weight, net	0.4 kg 0.882 lb
-------------	-------------------

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system



* Footnotes

Insertion Loss, typical	0.05√freq (GHz) (not applicable for elliptical waveguide)
-------------------------	---