



L4-HMHH-15-SGW-D

D-CLASS LDF4-50A SureFlex® Jumper with interface types 4.3-10 Male and 4.3-10 Male with HELIAX® SureGuard weatherproofing, 15 ft

- If there are threads along the entire device port length, the HELIAX® SureGuard weatherproofing solutions will only seal properly if the HSG-M29-ADPT adapter is installed on the device port

Logo Image



General Specifications

Body Style, Connector A	Straight
Body Style, Connector B	Straight
Cable Family	LDF4-50A
Interface, Connector A	4.3-10 Male
Interface, Connector B	4.3-10 Male
Nominal Size	1/2 in
Weatherproofing Method	HELIAX® SureGuard weatherproofing boot
Length	4.572 m 15.000 ft
Includes	Weatherproofing boot
Specification Sheet Revision Level	A

Electrical Specifications

3rd Order IMD Dynamic	-162.00 dBc (relative to carrier) -119.00 dBm
3rd Order IMD Dynamic Test Method	Two +43 dBm carriers per IEC 62037
DTF, Connector A	-34.00 dB
DTF, Connector B	-34.00 dB

Jumper Assembly Sample Label

L4-HMHM-15-SGW-D



Return Loss/VSWR

Frequency Band	VSWR	Return Loss (dB)
3.41–4.0 GHz	1.11	26.00
698–960 MHz	1.07	30.00
1700–2200 MHz	1.07	30.00
2200–2700 MHz	1.08	28.00

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant by Exemption
China RoHS SJ/T 11364-2006	Above Maximum Concentration Value (MCV)
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

