



PTS1P-NMNM-2M-P

PTS1-50-P SureFlex® Jumper with interface types N Male and N Male, 2M

General Specifications

Body Style, Connector A	Straight
Body Style, Connector B	Straight
Cable Family	PTS1-50-P
Interface, Connector A	N Male
Interface, Connector B	N Male
Nominal Size	1/4 in
Length	2.000 m 6.562 ft
Specification Sheet Revision Level	A

Electrical Specifications

3rd Order IMD Static	-153.00 dBc (relative to carrier) -110.00 dBm
3rd Order IMD Static Test Method	Two +43 dBm carriers

Jumper Assembly Sample Label

Batch: 0123456789 | Manufacturing Date (two digit year and week): US22 1240 | Manufacturing Plant: A | Product Revision: A

COMMSCOPE Andrew Solutions™
F4A-DMDM-2M-P (Part Number)
 2 M (6.562 FT)
 SUREFLEX ASSEMBLY
 U.S. PATENT 5802710
 Product of UNITED STATES
 12US220001242 (Serial Number)

Return Loss/VSWR

Frequency Band	VSWR	Return Loss (dB)
698–960 MHz	1.15	23.00
1700–2200 MHz	1.15	23.00
2200–2700 MHz	1.15	23.00

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant by Exemption
China RoHS SJ/T 11364-2006	Above Maximum Concentration Value (MCV)

Product Specifications

PTS1P-NMNM-2M-P

