

245173



Cold shrink Kit for 16 mm (0.62 in) to 10.54 mm (0.41 in) connections

Product Classification

| | |
|----------------------|------------------------------|
| Product Type | Cold shrink kit |
| Product Brand | HELIAX® |
| Ordering Note | ANDREW® non-standard product |

General Specifications

| | |
|--------------------|---|
| Application | Provides additional moisture seal for cable connections |
| Color | Black |

Dimensions

| | |
|---|----------------------|
| Length | 202.946 mm 7.99 in |
| Cable Diameter for Seal, maximum | 16 mm 0.63 in |
| Cable Diameter for Seal, minimum | 10.54 mm 0.415 in |
| Inner Diameter | 53.09 mm 2.09 in |

Material Specifications

| | |
|----------------------|-------------|
| Material Type | EPDM rubber |
|----------------------|-------------|

Environmental Specifications

| | |
|---|--|
| UV Resistance Test Method | UV condensation reference ASTM-G-53, light source UVA 340 fluorescent lamp |
| UV Resistance, minimum with no degradation | ≥1000 hours |
| Weather Resistance Test Method | 04AS00-03.6.0 IEC 60529:2001, IP67 MIL-STD-1344A, Method 1002 |

Packaging and Weights

| | |
|-----------------------|---------------------|
| Height, packed | 299.72 mm 11.8 in |
| Width, packed | 76.2 mm 3 in |
| Length, packed | 76.2 mm 3 in |

245173

| | |
|---------------------------|--|
| Included | One EPDM rubber tube Two sealing foam strips |
| Packaging quantity | 1 |
| Weight, gross | 0.14 kg 0.309 lb |

Regulatory Compliance/Certifications

| Agency | Classification |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| REACH-SVHC | Compliant as per SVHC revision on www.commscope.com/ProductCompliance |
| ROHS | Compliant |
| UK-ROHS | Compliant |