

# CSG12-12B2U

---



SureGround® Universal Compact Grounding Kit for 1/2 in corrugated and smoothwall coaxial cable

## Product Classification

<b>Product Type</b>	Grounding kit
<b>Product Brand</b>	SureGround®
<b>Ordering Note</b>	ANDREW® standard product (Global)

## General Specifications

<b>Bonding Conductor Jacketing Material</b>	PVC
<b>Bonding Conductor Material</b>	Copper
<b>Bonding Conductor Wire Size</b>	16 mm <sup>2</sup>
<b>Cable Type</b>	Corrugated   Smoothwall
<b>Color</b>	Black
<b>Grounding Kit Type</b>	Compact SureGround® Grounding Kits
<b>Grounding Strap Material</b>	Tinned copper
<b>Lug Attachment</b>	Field attached
<b>Lug Type</b>	Two-hole lug
<b>Thread Size</b>	3/8 in

## Dimensions

<b>Enclosure Width</b>	25.4 mm   1 in
<b>Bonding Conductor Length</b>	1143 mm   45 in
<b>Enclosure Length</b>	55.88 mm   2.2 in
<b>Compatible Diameter, maximum</b>	16.256 mm   0.64 in
<b>Compatible Diameter, minimum</b>	15.367 mm   0.605 in
<b>Nominal Size</b>	1/2 in

# CSG12-12B2U

---

## Electrical Specifications

<b>Current Handling</b>	Tested to withstand 100,000 amps peak current surge
<b>Current Handling Test Method</b>	MIL-STD-1757
<b>Grounding, Bonding and Shielding Test Method</b>	MIL-STD-188-124A
<b>Lightning Protection Test Method</b>	IEC 1024-1

## Material Specifications

<b>Locking Bail Material</b>	Stainless steel
<b>Rivet Material</b>	Tinned copper

## Environmental Specifications

<b>Operating Temperature</b>	-40 °C to +85 °C (-40 °F to +185 °F)
<b>Storage Temperature</b>	-40 °C to +80 °C (-40 °F to +176 °F)
<b>Blowing Rain Test Method</b>	MIL-STD-810, Method 506
<b>Corrosion Test Method</b>	MIL-STD-1344, Method 1001
<b>Freezing Rain/Icing Test Method</b>	MIL-STD-810, Method 521
<b>Humidity Test Method</b>	MIL-STD-1344, Method 1002
<b>Immersion Test Method</b>	IEC 60529:2001, IP68
<b>UV Resistance Test Method</b>	MIL-STD-810, Method 505
<b>Vibration Test Method</b>	MIL-STD-202, Method 214
<b>Weatherproofing Method</b>	Tinned copper strap contact overmolded with EPDM rubber

## Packaging and Weights

<b>Height, packed</b>	304.8 mm   12 in
<b>Width, packed</b>	279.4 mm   11 in
<b>Length, packed</b>	25.4 mm   1 in
<b>Included</b>	Grounding kit   Hardware   Lug
<b>Packaging quantity</b>	1
<b>Weight, gross</b>	0.23 kg   0.507 lb

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
CHINA-ROHS	Below maximum concentration value

# CSG12-12B2U

---

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a>
ROHS	Compliant
UK-ROHS	Compliant



## \* Footnotes

<b>Grounding, Bonding and Shielding Test Method</b>	Military Standard for Grounding, Bonding, and Shielding: Bond Resistance Requirement of a Maximum dc resistance of 0.001 ohm
<b>Lightning Protection Test Method</b>	Protection Against Lightning Electromagnetic Impulse, Table 1—Protection Level III–IV, 1995-02