



## FJ-4SM-008-75M

**Heliax® FiberFeed® tail, Bend Insensitive Singlemode Fiber DLC to DLC 4-Fiber Distribution Cable, riser, black jacket, 75 m**

### Construction Materials

Fiber Type	Bend insensitive singlemode fiber (G.657.A2)
Total Fibers, quantity	4
Jacket Color	Black

### Dimensions

Cord Length	75.00 m		246.06 ft
Breakout Length, Fiber, end 1	700 mm		28 in
Breakout Length, Fiber, end 2	250 mm		10 in

### Environmental Specifications

Environmental Space	Wireless installation
Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)

### General Specifications

Construction Type	Discrete fiber tail
Interface Body Style, connector A	Straight
Interface Body Style, connector B	Straight
Interface Feature, connector A	Standard
Interface Feature, connector B	Standard
Interface, connector A	DLC
Interface, connector B	DLC
Minimum Bend Radius, furcation	30.0 mm   1.2 in

### Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system



### Included Products

760170993 | Z-004-MP-8G-M60BK (Product Component—not orderable) — Indoor/Outdoor Low Smoke Zero Halogen Riser MPO Trunk Cable, 4 fiber

- CS-8G-MP (Product Component—not orderable) — Enhanced Low Macrobending, Zero Water Peak, Dispersion-Unshifted Singlemode Fiber (ITU-T G.657.A2, B2)