

L1SGRIP



Support Hoisting Grip with clamp for 0.32-0.44 in (8.2-11.2 mm) coaxial cable

Product Classification

| | |
|----------------------|------------------------------|
| Product Type | Hoisting grip |
| Product Brand | HELIAX® |
| Ordering Note | ANDREW® non-standard product |

General Specifications

| | |
|-------------------------------------|------------------------|
| Attachment Spacing Intervals | 60.96 m 200 ft |
| Hoisting Grip Type | Support hoisting grip |
| Installation Tool | Required, not included |
| Support Clamp | Included |
| Tool Type | Hoisting grip |

Dimensions

| | |
|-------------------------------------|--------------------|
| Grip Length, minimum | 101.6 mm 4 in |
| Leader Length, minimum | 152.4 mm 6 in |
| Compatible Diameter, maximum | 11.2 mm 0.441 in |
| Compatible Diameter, minimum | 8.2 mm 0.323 in |
| Nominal Size | 1/4 in |

Electrical Specifications

| | |
|------------------------------------|--------|
| Return Loss Effect, maximum | 0.1 dB |
| DTF Effect, maximum | 0.1 dB |

Material Specifications

| | |
|----------------------|-------------------------------------|
| Material Type | Stainless steel Tin-coated bronze |
|----------------------|-------------------------------------|

Mechanical Specifications

| | |
|---------------------------|---------------------|
| Pull Load Capacity | 158.757 kg 350 lb |
|---------------------------|---------------------|

L1SGRIP

Packaging and Weights

| | |
|---------------------------|-------------------|
| Height, packed | 25.4 mm 1 in |
| Width, packed | 177.8 mm 7 in |
| Length, packed | 127 mm 5 in |
| Packaging quantity | 1 |
| Weight, gross | 0.3 kg 0.661 lb |

Regulatory Compliance/Certifications

| Agency | Classification |
|---------------|--|
| CHINA-ROHS | Below maximum concentration value |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| REACH-SVHC | Compliant as per SVHC revision on www.commscope.com/ProductCompliance |
| ROHS | Compliant |
| UK-ROHS | Compliant |

