



RFFT-36SM-001-75M

Bend Insensitive Singlemode Fiber DLC to DLC 36-Fiber Cable Assembly with pulling grip, 75 m

Construction Materials

Fiber Type	Bend insensitive singlemode fiber (G.657.A1)
Total Fibers, quantity	36
Furcation Color	Yellow
Jacket Color	Black

Dimensions

Cord Length	75.00 m 246.06 ft
Breakout Length, Fiber, end 1	1 m 3 ft
Breakout Length, Fiber, end 2	2 m 7 ft

Environmental Specifications

Environmental Space	Riser Wireless installation
Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)

General Specifications

Construction Type	Discrete fiber trunk
Cable Glands	No glands
Color, connector A	Blue
Color, connector B	Blue
Interface Body Style, connector A	Straight
Interface Body Style, connector B	Straight
Interface Feature, connector A	Uniboot
Interface Feature, connector B	Uniboot
Interface, connector A	DLC
Interface, connector B	DLC
Minimum Bend Radius, furcation	30.0 mm 1.2 in
Pulling Grips, quantity	1

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system



Included Products

RFFT-36SM-001-75M

POWERED BY



760171959 | R-036-CN-8G-F12BK — Indoor/Outdoor Single Jacket All-Dielectric Riser Rated Central Tube Cable

- CS-8G-LT (Product Component—not orderable) — Enhanced Low Macrobending, Zero Water Peak, Dispersion-Unshifted Singlemode Fiber (ITU-T G.657.A2, B2)