

# SSH-1416



SnapTak PIM-guard Adjustable Hanger for 14.1 mm to 16.0 mm Cable – PIM Free Polymer Construction. No Grommets Required.

## Product Classification

|                     |                   |
|---------------------|-------------------|
| <b>Brand</b>        | SnapTak PIM-guard |
| <b>Product Type</b> | Hanger kit        |

## Dimensions

|                                     |                      |
|-------------------------------------|----------------------|
| <b>Compatible Diameter, maximum</b> | 16.000 mm   0.630 in |
| <b>Compatible Diameter, minimum</b> | 14.100 mm   0.555 in |
| <b>Height</b>                       | 32.13 mm   1.26 in   |
| <b>Length</b>                       | 31.50 mm   1.24 in   |
| <b>Width</b>                        | 31.50 mm   1.24 in   |

## Electrical Specifications

|                           |        |
|---------------------------|--------|
| <b>DTF Effect</b>         | 0.1 dB |
| <b>Return Loss Effect</b> | 0.1 dB |

## Environmental Specifications

|                              |                                      |
|------------------------------|--------------------------------------|
| <b>Operating Temperature</b> | -40 °C to +85 °C (-40 °F to +185 °F) |
|------------------------------|--------------------------------------|

## General Specifications

|                                      |   |
|--------------------------------------|---|
| <b>Hanger Type</b>                   | Snap-in hanger  |
| <b>Cables per Hanger</b>             | 1   |
| <b>Color</b>                         | Black   |
| <b>CommScope Accessories</b>         | Hangers   |
| <b>Material Type</b>                 | Engineered plastic  |
| <b>Maximum Stack Height</b>          | 3   |
| <b>Maximum Stack Height, Coaxial</b> | 3   |
| <b>Ordering Note</b>                 | CommScope® standard product in Asia Pacific   CommScope® standard product in Mexico, Central America, and South America   CommScope® standard product in the United States and Canada |

Package Quantity 10

## Mechanical Specifications

**Mounting** 3/4 in drilled cable ladder  
**UV Resistance, minimum with no degradation** =1000 hours exposure in accelerated UV life chamber  
**Vibration Survival** =4 hours at resonant frequency  
**Environmental Strength Capability** Double cable weight

## Packed Dimensions

**Height** 30.5 mm | 1.2 in  
**Length** 254.0 mm | 10.0 in  
**Shipping Weight** 0.54 kg | 1.19 lb  
**Width** 203.2 mm | 8.0 in

## Regulatory Compliance/Certifications

| Agency        | Classification   |
|---------------|--|
| ISO 9001:2008 | Designed, manufactured and/or distributed under this quality management system |

## \* Footnotes

**Maximum Stack Height** Fiber, Hybrid, Power